

Omnisports

TECHNICAL DATA	STANDARD	COMPACT	SPEED	TRAINING	REFERENCE MULTI-USE	ACTIVE	EXCEL	PUREPLAY
CERTIFICATION & CLASSIFICATION								
Type of floor covering	EN 14041	Heterogeneous compact indoor floorcoverings	Heterogeneous indoor floorcoverings	Heterogeneous indoor floorcoverings	-	-	-	-
	EN 14904	-	-	-	Heterogeneous indoor sport floorcoverings	Heterogeneous indoor sport floorcoverings	Heterogeneous indoor sport floorcoverings	Heterogeneous indoor sport floorcoverings
Declaration of Performance	EN 14041	0120-003-DoP-2013-04	0120-006-DoP-2013-04	0120-026-DoP-2013-04	-	-	-	-
	EN 14904	-	-	-	0120-080-DoP-2018-11	0120-076-DoP-2017-10	0120-041-DoP-2013-04	0120-071-DoP-2016-04
TECHNICAL CHARACTERISTICS								
Total thickness	ISO 24346 (EN 428)	2 mm	3.45 mm	5 mm	6.1 mm	7.1 mm	8.3 mm	9.4 mm
Total weight	ISO 23997 (EN 430)	3 045 g/m ²	3 295 g/m ²	4 080 g/m ²	3950 g/m ²	4795 g/m ²	6 095 g/m ²	6 200 g/m ²
Width	ISO 24341 (EN 426)	2 m	2 m	2 m	2 m	2 m	2 m	2 m
Length	ISO 24341 (EN 426)	23 lm	20.5 lm	20.5 lm	20.5 lm	20.5 lm	20.5 lm	20.5 lm
REQUIREMENTS FOR USE								
Shock absorption	Average measured value	-	≥ 4%	≥ 17%	P1	P1	P1	P2
	EN 14808 requirement	-	-	-	≥ 25%	≥ 25%	≥ 25%	≥ 35%
Friction	Average measured value	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant
	EN 13036-4 requirement	80 to 110	80 to 110	80 to 110	80 to 110	80 to 110	80 to 110	80 to 110
Vertical deformation	Average measured value	-	≤ 0.8 mm	≤ 1 mm	P1	P1	P1	P2
	EN 14809 requirement	-	≤ 5 mm	≤ 5 mm	≤ 2 mm	≤ 2 mm	≤ 2 mm	≤ 3 mm
TECHNICAL REQUIREMENTS								
Vertical ball behaviour	Average measured value	-	Compliant	Compliant	Compliant	Compliant	Compliant	Compliant
	EN 12235 requirement	-	≥ 90%	≥ 90%	≥ 90%	≥ 90%	≥ 90%	≥ 90%
Reaction to fire	EN 13501-1	B _{fl} s1*	C _{fl} s1*	C _{fl} s1*	C _{fl} s1**	C _{fl} s1**	C _{fl} s1**	C _{fl} s1**
Resistance to wear	EN ISO 5470-1	-	≤ 1g	≤ 1g	≤ 1g	≤ 1g	≤ 1g	≤ 1g
Resistance to indentation	Average measured value	-	≤ 0.18 mm	≤ 0.16 mm	≤ 0.10 mm	≤ 0.15 mm	≤ 0.15 mm	Compliant
	EN 1516 requirement	-	≤ 0.50 mm	≤ 0.50 mm	≤ 0.50 mm	≤ 0.50 mm	≤ 0.50 mm	≤ 0.50 mm
Resistance to a rolling load	Average measured value	-	-	Compliant	Compliant	Compliant	Compliant	Compliant
	EN 1569 requirement	-	-	≤ 0.5 mm	≤ 0.5 mm	≤ 0.5 mm	≤ 0.5 mm	≤ 0.5 mm
In room noise	NFS 31-074	-	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB	Class A ≤ 65dB
Thermal resistance	EN ISO 10456	Approx. 0.02 m ² K/W	Approx. 0.05 m ² K/W	Approx. 0.07 m ² K/W	Approx. 0.09 m ² K/W	Approx. 0.10 m ² K/W	Approx. 0.12 m ² K/W	Approx. 0.14 m ² K/W
ENVIRONMENTAL PERFORMANCES								
Total VOC emissions	ISO 16000-9	≤ 10 µg/m ³ (after 28 days)	≤ 10 µg/m ³ (after 28 days)	≤ 10 µg/m ³ (after 28 days)	≤ 10 µg/m ³ (after 28 days)	≤ 10 µg/m ³ (after 28 days)	≤ 10 µg/m ³ (after 28 days)	≤ 10 µg/m ³ (after 28 days)
COLOURS								
		Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8	Uni: 16 / Wood: 8

The above information is subject to modification for the benefit of further improvement. (12/18). *Glued installation **GreenLay installation
Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

Compact

Speed

Training

Reference Multi-Use

Active

Excel

PurePlay

They certified Tarkett Omnisports

GreenLay

(1) Available for Reference Multi-Use, Active, Excel & Pureplay

Restart Ready

Top Clean XP PUR REINFORCED

WESTERN EUROPE: Austria: Tarkett Holding GmbH, Niederlassung Wien - Tel. +43 1 47 88 062 ■ Belgium: Tarkett Belux Sprl - Tel. +32 16 35 98 80 ■ Denmark: Tarkett A/S - Tel. +45 43 90 60 11 ■ Finland: Tarkett Oy - Tel. +358 9 4257 9000 ■ France: Tarkett SAS - Tel. +33 1 41 20 42 49 ■ Germany: Tarkett Holding GmbH - Tel. +49 62 33 810 ■ Greece: Tarkett Monoprosopi Ltd - Tel. +30 210 6745 340 ■ Italy: Tarkett S.p.A. - Tel. +39 0744 7551 ■ Luxembourg: Tarkett GDL SA - Tel. +352 949 211 8804 ■ Netherlands: Tarkett BV - Tel. +31 416 685 491 ■ Norway: Tarkett AS - Tel. +47 32 20 92 00 ■ Portugal: Tarkett SA - Tel. +351 21 427 64 20 ■ Spain: Tarkett Floors S.L. - Tel. +34 91 358 00 35 ■ Sweden: Tarkett Sverige AB - Tel. +46 771 25 19 00 ■ Switzerland: Tarkett Holding GmbH - Tel. +41 043 233 79 24 ■ Turkey: Tarkett Aspen - Tel. +90 212 213 65 80 ■ United Kingdom: Tarkett Ltd - Tel. +44 (0) 1622 854 040 ■ **EASTERN EUROPE:** Baltic Countries: Tarkett Baltics: Tel. +370 37 262 220 ■ Czech Republic: Tarkett org. složka - Tel. +420 271 001 600 ■ Hungary: Tarkett Polska SP Z.O.O. magyarországi fióktelepe - Tel. +36 1 437 8150 ■ Poland: Tarkett Polska Sp. z o.o. - Tel. +48 22 16 09 231 ■ Russian Federation: ZAO Tarkett RUS - Tel. +7 495 775 3737 ■ Slovakia: Tarkett Polska, organizačná zložka - Tel. +421 2 48291 317 ■ South East Europe: Tarkett SEE - Tel. +381 21 7557 649 (44) 569 12 21 ■ Ukraine: Tarkett UA - Tel. +38 (0) 44 569 12 21 ■ **ASIA AND OCEANIA:** Australia: Tarkett Australia Pty Ltd - Tel. +61 2 88 53 12 00 ■ China: Tarkett Floor Covering (Shanghai) Co. Ltd. - Tel. +86 (21) 60 95 68 38 ext 841 ■ North East Asia: Tarkett Hong Kong Limited - Tel. +852 2511 8716 ■ India: Tarkett Flooring India Pvt. Ltd. - Bangalore - Tel. +91 80 4130 3793 - New Delhi - Tel. +91 11 4352 4073 - Mumbai - Tel. +91 22 2648 8750 ■ South East Asia: Tarkett Flooring Singapore Pte. Ltd. - Tel. +65 6346 1585 ■ **AFRICA:** Tarkett International: Tel. +33 1 41 20 41 01 ■ **MIDDLE EAST:** Tarkett Middle East: Tel. +961 1 51 3363/4 ■ Israel: Tarkett International: Tel. +33 1 41 20 41 01
NORTH AMERICA: USA: Tarkett Inc. - Tel. +1 713 869 5811 / Johnsonite - Tel. +1 440 543 8916 ■ Canada: Tarkett Inc. - Tel. +1 450 293 173 ■ **LATIN AMERICA:** Brazil: Tarkett - Tel. 55 12 3954 7108 ■ Argentina - Chile - Uruguay: Tarkett Latam Mercosur - Tel. +54 11 47 08 07 72 / +54 9 11 44 46 88 82 ■ Bolivia - Colombia - Ecuador - Panama - Paraguay - Peru - Trinidad and Tobago - Venezuela: Tarkett - Tel. +55 11 9 8410 9310 / +55 11 95494 0069 ■ Mexico / Central America: Tarkett Latam Mexico - Tel. +55 11 98410 9310